

Challenger

3400

Standard Features

Five Section Tower Mast.
 Double Acting Hydraulic Cylinder.
 4' x 12' Fiberglass Work Platform.
 5000 Volt Rating. (5 KV)
 1000 lb. Platform Capacity.
 42" Folding Hand Rails.
 360 Degree Full Rotation.
 Electric/Hydraulic Open Center Full Hydraulic System.
 5-Air Operated Platform Controls.
 Deadman Safety Lockout Feature.
 Emergency Override Feature.
 Painted Steel- Gloss Black
 Fiberglass Platform-Natural Green.
 Meets or exceeds ANSI A92.2 (1990) and OSHA Standards.

Minimum Chassis GVWR

84" Cab to Axle.
 Front Axle - 8000 lb.
 Rear Axle - 15,000 lb.

Optional Equipment

Outriggers (required on 3435 model)
 Oversized & Offset Platforms.
 Remote Controls (Start-Stop, Emergency Power, etc.)
 Hydraulic or Air Tool Outlets @ Platform.
 Reinforced Rails & Rail Cutouts.
 Ladders for access: Fixed or Telescoping.
 Special Paint.

Note: For detailed specifications or additional Information, contact your local **Challenger** Dealer or contact factory sales @ 765-564-2212.

Challenger Aerial Towers are a product of:

DELPHI BODY WORKS INC.

313 South Washington St.
 P.O.Box 30
 Delphi, Indiana 46923
 Phone: 765-564-2212
 Fax: 765-564-4255
 E-mail: dbw1@carlnet.org

Distributed by:

